



**100% SYNTHETIC
DIESEL CJ4**

FEATURES & BENEFITS

Meets or exceeds the following requirements:

- API CJ-4, CI-4 Plus, CI-4, SN, SL
- CAT ECF-2
- CAT ECF-3
- CAT ECF-1-a
- CUMMINS CES 20081
- Detroit Diesel DDC 93K218
- Mack EO-O Premium Plus
- Volvo VDS-4
- Renault Truck RLD-3C4
- Excellent cold and start up protection
- Prevents high heat volatility
- Broad operating temperature protection
- Enhanced Extended drain capabilities



PUREZONE SYNTHETIC 5W-40 is highly advanced full synthetic performance diesel engine oil formulated using high quality synthetic base stocks and a specially engineered additive package. Formulated for the extreme conditions of the toughest jobs, **PUREZONE SYNTHETIC 5W-40** provides top tier protection no matter what environment your equipment is operating in.

PUREZONE SYNTHETIC 5W-40 provides superior soot control caused by the higher operating temperatures of EGR and DPF equipped engines. The low SAPS formulation is compatible with all 2007 EPA compliant diesel engines as well as backwards compatible with previous API categories. **PUREZONE SYNTHETIC 5W-40** is also well suited for extended drain capabilities making it more economical than conventional diesel oil which means better reliability, less down time, less consumption and ultimately less maintenance costs. Using less oil is also better for the environment.

TYPICAL RESULTS

Testing Parameter	5W40
DENSITY @ 15°C(ASTM D4052) kg/L	0.8513
VISCOSITY (D-445) cSt @ 40°C	90
VISCOSITY (D-445) cSt @ 100°C	14
VISCOSITY INDEX (D-2270)	160
POUR POINT (°C) (D-97)	-48
FLASH POINT (°C) (D-92)	242
COLD CRANK SIMULATOR (D-5293) cP@ (°C)	6200@-30
TOTAL BASE NUMBER	9.1

ORDER CODES

5W40
946ML / 1 US Qt HDS540946
5L / 1.33 US G HDS5405
18.9L / 5 US G HDS540189
205L / 54.2 US G HDS540205